

SAFETY & QUALITY

AURA has proven his Safety & Quality by achieving Europe Standards with TÜV certificate.

It is equipped with;

- 2 Circuit Breaker Thermostats for overheating (Reset Type).
- A high sensitive Micro controlled Diaphragm system
- A high pressure safety switch and is being tested under 12 Bar pressure.
- A rotary safety switch.
- A Resistance that is prevented to contact with water by SS tube and MgO.

PROVEN TRACK RECORD

Since its introduction to the market in 1990, the AURA name has become synonymous with quality and reliability. You can use in Apartment buildings, Homes, Businesses, Universities, Hospitals and Hotels.

LONG LIFE CYCLE & HEALTHY

Aura Water Heaters can last more than 20 years. Because of they don't have any Metal Tank inside to cause Rust and Scalding. Therefore it is not causing skin allergies and falling of hair.

ENERGY SAVINGS OF UP TO 60%

AURA operates only when you open Hot water Tab in your home. When you close your Hot Water Tab, it stops using electricity. But in conventional tank-type heaters, the water is kept heated 24 hours; even when you are asleep or at work.

ENJOY ENDLESS SHOWERS

Never run out of hot water again, you can enjoy long hot showers with AURA, because your water is heated instantly. Traditional heaters are limited to the amount of hot water they can provide by the size of its tank. It is sure that you will run out of hot water after 2 showers.

HEAT YOUR ENTIRE HOME

One unit of AURA will provide all your need of hot water for your BATHROOM AND KITCHEN at the same time.

ihlas
Ev Aletleri

B.O.S.B Mermereiler Sanayi Sitesi
7.Cadde No:14 Beylikdüzü - İSTANBUL
Tel : 0212 875 35 62 Faks : 0212 875 36 64
www.iea.com.tr - info@iea.com.tr

aura

Water Heaters



CE

848027ZLF



MODEL
105MC

microControl

Features

- Multi safe (5safety features)
- Tubular heating element SS (Copper optional)
- Double thermostat
- Adjustable power (3-4-7 kW)
- Shower set
- Installation kits



MODEL
105DJ

magneticControl

Features

- Digital controller
- Multi safe (5safety features)
- Temperature and level display
- Magnetic flow sensor
- Tubular heating element SS (Copper optional)
- Double thermostat
- Adjustable power (3-4-7 kW)
- Shower set
- Installation kits



MODEL
105A5

Basic

Features

- Multi safe (5safety features)
- Tubular heating element SS (Copper optional)
- Single thermostat
- Adjustable power (3-4-7 kW)
- Shower set
- Installation kits



TECHNICAL FEATURES

Power	: 7 kW
Voltage	: 230 V AC, 50-60 Hz
Flow Rate	: 4 L/min
Nominal Pressure	: 0 Pa
Min. Operating Pressure	: 25 kPa (2.5mmSS)
Max. Operating Pressure	: 600 kPa (61mmSS)
Protection Class	: I
IP Code	: IP44

SHIPPING INFORMATION

Box Size	: 360 x 220 x 180 mm
Carton Size (6 units/carton)	: 540 x 460 x 390 mm
Carton Weight	: 3 Kg
Qty/20' Container	: 1800 Units / 300 Carton
Qty/40' Container	: 3960 Units / 660 Carton
Qty/40' HQ Container	: 4620 Units / 770 Carton

TECHNICAL FEATURES

Power	: 7 kW
Voltage	: 230 V AC, 50-60 Hz
Flow Rate	: 4 L/min
Nominal Pressure	: 0 Pa
Min. Operating Pressure	: 10 kPa (1mmSS)
Max. Operating Pressure	: 600 kPa (61mmSS)
Protection Class	: I
IP Code	: IP44

SHIPPING INFORMATION

Box Size	: 360 x 220 x 180 mm
Carton Size (6 units/carton)	: 540 x 460 x 390 mm
Carton Weight	: 3 Kg
Qty/20' Container	: 1800 Units / 300 Carton
Qty/40' Container	: 3960 Units / 660 Carton
Qty/40' HQ Container	: 4620 Units / 770 Carton

TECHNICAL FEATURES

Power	: 7 kW
Voltage	: 230 V AC, 50-60 Hz
Flow Rate	: 4 L/min
Nominal Pressure	: 0 Pa
Min. Operating Pressure	: 25 kPa (2.5mmSS)
Max. Operating Pressure	: 600 kPa (61mmSS)
Protection Class	: I
IP Code	: IP34

SHIPPING INFORMATION

Box Size	: 360 x 240 x 170 mm
Carton Size (6 units/carton)	: 540 x 460 x 380 mm
Carton Weight	: 3 Kg
Qty/20' Container	: 1500 Units / 300 Carton
Qty/40' Container	: 3300 Units / 660 Carton
Qty/40' HQ Container	: 3850 Units / 770 Carton