



TÜRBOSAN

FIRE PUMPS & FIRE PUMP SETS



50 Hz UL/FM Fire Pumps :

50 GPM, 100 GPM, 150 GPM, 200 GPM,
250 GPM, 300 GPM, 400 GPM, 450 GPM,
500 GPM, 750 GPM, 1000 GPM, 1250 GPM,
1500 GPM, 2000 GPM, 2500 GPM, 3000 GPM

UL Listed Fuel Tanks:

300 Lt, 610 Lt, 910 Lt, 1260 Lt

60 Hz UL Listed Fire Pumps:

300 GPM, 400 GPM, 450 GPM, 500 GPM,
750 GPM, 1250 GPM, 1500 GPM

We use internationally accepted UL Listed and FM Approved brands for Electric Motor, Diesel Engine and Control Panel.

Your work area and life safety are secured with the Fire Fighting Pump systems that we manufacture.
We use first-class materials.

Attention: Do not use fire pumps for any other purpose.



📍 Makine İhtisas OSB. 5. Cad. No:33 Dilovası 41455 Kocaeli/ TÜRKİYE ✉ export@turbosan.com

☎ +90 262 722 95 40

🌐 www.turbosan.com



TÜRBOSAN TURBOMAKİNALAR SANAYİ VE TİCARET A.Ş.						
UL 448 - UL LISTED 60 Hz PUMPS						
EX 26604						
CENTRIFUGAL FIRE PUMPS, END SUCTION (QWZU)				Approx Speed (rpm)	3570 rpm	
Rated Capacity Q (gpm)	Rated Capacity Q (m ³ /h)	Size (in.)	PUMP Model	TENTATIVE Rated Net Pressure Range Hm (psi)	TENTATIVE Rated Net Pressure Range Hm (mwc)	TENTATIVE Max Working Pressure (psi)
300	68	4x3	NORM EFF 80/200A	91-153	64,0 - 107,6	210
400	91	4x3	NORM EFF 80/200A	86-149	60,5 - 104,7	210
450	102	4x3	NORM EFF 80/200A	83-147	58,3 - 103,3	210
500	114	4x3	NORM EFF 80/200A	81-144	56,9 - 101,2	210
750	170	6x4	NORM EFF 125/200	82-133	57,6 - 93,5	210
1000	227	6x4	NORM EFF 125/200	80-134	56,2 - 94,2	210
1250	284	6x4	NORM EFF 125/200	76-131	53,4 - 92,1	210
1500	341	6x4	NORM EFF 125/200	64-124	45,0 - 87,2	210
750	170	6x5	NORM SN 125/250	124-194	87,2 - 136,4	261
1000	227	6x5	NORM SN 125/250	123-195	86,5 - 137,1	261
1250	284	6x5	NORM SN 125/250	122-194	85,8 - 136,4	261
1500	341	6x5	NORM SN 125/250	116-193	81,5 - 135,7	261
750	170	5x4	NORM SN 100/250	121-213	85,1 - 149,7	261
1000	227	5x4	NORM SN 100/250	121-214	85,1 - 150,4	261
1250	284	5x4	NORM SN 100/250	114-213	80,1 - 149,7	261
1500	341	5x4	NORM SN 100/250	107-210	75,2 - 147,6	261
EX 26605						
CENTRIFUGAL FIRE PUMPS, SPLIT CASE (QXJY)				Approx Speed (rpm)	3570 rpm	
Rated Capacity Q (gpm)	Rated Capacity Q (m ³ /h)	Size (in.)	PUMP Model	TENTATIVE Rated Net Pressure Range Hm (psi)	TENTATIVE Rated Net Pressure Range Hm (mwc)	TENTATIVE Max Working Pressure (psi)
500	114	6x4	CEP 100/250	150-223	105,5 - 156,8	290
750	170	6x4	CEP 100/250	143-223	100,5 - 156,8	290
1000	227	6x4	CEP 100/250	134-219	94,2 - 154,0	290
1250	284	6x4	CEP 100/250	123-210	86,5 - 147,6	290

